



UNITED STATES PATENT AND TRADEMARK OFFICE

UNITED STATES DEPARTMENT OF COMMERCE
United States Patent and Trademark Office
Address: COMMISSIONER FOR PATENTS
P.O. Box 1450
Alexandria, Virginia 22313-1450
www.uspto.gov

| APPLICATION NO. | FILING DATE | FIRST NAMED INVENTOR | ATTORNEY DOCKET NO. | CONFIRMATION NO. |
|-----------------|-------------|----------------------|---------------------|------------------|
|-----------------|-------------|----------------------|---------------------|------------------|

10/584,616

06/26/2006

Shinji Saitou

060482

9654

21874

7590

09/10/2008

EDWARDS ANGELL PALMER & DODGE LLP

P.O. BOX 55874

BOSTON, MA 02205

EXAMINER

GILMAN, ALEXANDER

ART UNIT

PAPER NUMBER

2833

MAIL DATE

DELIVERY MODE

09/10/2008

PAPER

Please find below and/or attached an Office communication concerning this application or proceeding.

The time period for reply, if any, is set in the attached communication.

| | | | |
|------------------------------|--|--------------------------------------|--|
| Office Action Summary | Application No. 10/584,616 | Applicant(s) SAITOU ET AL. | |
| | Examiner Alexander D. Gilman | Art Unit 2833 | |

-- The MAILING DATE of this communication appears on the cover sheet with the correspondence address --

Period for Reply

A SHORTENED STATUTORY PERIOD FOR REPLY IS SET TO EXPIRE 3 MONTH(S) OR THIRTY (30) DAYS, WHICHEVER IS LONGER, FROM THE MAILING DATE OF THIS COMMUNICATION.

- Extensions of time may be available under the provisions of 37 CFR 1.136(a). In no event, however, may a reply be timely filed after SIX (6) MONTHS from the mailing date of this communication.
- If NO period for reply is specified above, the maximum statutory period will apply and will expire SIX (6) MONTHS from the mailing date of this communication.
- Failure to reply within the set or extended period for reply will, by statute, cause the application to become ABANDONED (35 U.S.C. § 133). Any reply received by the Office later than three months after the mailing date of this communication, even if timely filed, may reduce any earned patent term adjustment. See 37 CFR 1.704(b).

Status

- 1) ☒ Responsive to communication(s) filed on 26 June 2006.
- 2a) ☐ This action is **FINAL**. 2b) ☒ This action is non-final.
- 3) ☐ Since this application is in condition for allowance except for formal matters, prosecution as to the merits is closed in accordance with the practice under *Ex parte Quayle*, 1935 C.D. 11, 453 O.G. 213.

Disposition of Claims

- 4) ☒ Claim(s) 12-22 is/are pending in the application.
- 4a) Of the above claim(s) _____ is/are withdrawn from consideration.
- 5) ☐ Claim(s) _____ is/are allowed.
- 6) ☒ Claim(s) 12-22 is/are rejected.
- 7) ☐ Claim(s) _____ is/are objected to.
- 8) ☐ Claim(s) _____ are subject to restriction and/or election requirement.

Application Papers

- 9) ☐ The specification is objected to by the Examiner.
- 10) ☐ The drawing(s) filed on _____ is/are: a) ☐ accepted or b) ☐ objected to by the Examiner.
Applicant may not request that any objection to the drawing(s) be held in abeyance. See 37 CFR 1.85(a).
Replacement drawing sheet(s) including the correction is required if the drawing(s) is objected to. See 37 CFR 1.121(d).
- 11) ☐ The oath or declaration is objected to by the Examiner. Note the attached Office Action or form PTO-152.

Priority under 35 U.S.C. § 119

- 12) ☐ Acknowledgment is made of a claim for foreign priority under 35 U.S.C. § 119(a)-(d) or (f).
- a) ☐ All b) ☐ Some * c) ☐ None of:
1. ☐ Certified copies of the priority documents have been received.
 2. ☐ Certified copies of the priority documents have been received in Application No. _____.
 3. ☐ Copies of the certified copies of the priority documents have been received in this National Stage application from the International Bureau (PCT Rule 17.2(a)).

* See the attached detailed Office action for a list of the certified copies not received.

Attachment(s)

- | | |
|--|---|
| 1) <input checked="" type="checkbox"/> Notice of References Cited (PTO-892) | 4) <input type="checkbox"/> Interview Summary (PTO-413) |
| 2) <input type="checkbox"/> Notice of Draftsperson's Patent Drawing Review (PTO-948) | Paper No(s)/Mail Date. _____ |
| 3) <input checked="" type="checkbox"/> Information Disclosure Statement(s) (PTO/SB/08) | 5) <input type="checkbox"/> Notice of Informal Patent Application |
| Paper No(s)/Mail Date <u>6/26/06;8/03/06</u> . | 6) <input type="checkbox"/> Other: _____ |

Art Unit: 2833

DETAILED ACTION

Claim Rejections - 35 USC § 102

The following is a quotation of the appropriate paragraphs of 35 U.S.C. 102 that form the basis for the rejections under this section made in this Office action:

A person shall be entitled to a patent unless –

(b) the invention was patented or described in a printed publication in this or a foreign country or in public use or on sale in this country, more than one year prior to the date of application for patent in the United States.

Claim 16,20, are rejected under 35 U.S.C. 102(b) as being anticipated by McQuade et al

With regard to claim 16, 20, WO 02/061443 – inv. McQuade et al

disclose an electrically conductive contact holder comprising: a supporting member (76,74) with an opening (54) formed therein; and an holder hole forming unit set (56) in the opening that includes a holder hole accommodating an electrically conductive contact electrically connected to an external connecting terminal provided on a to-be-contacted member, wherein

any one (74a) of the supporting member and the holder hole forming unit has a coefficient of linear expansion higher than that of the to-be-contacted member , while the other (56) has a coefficient of linear expansion lower than that of the to-be-contacted member.

Claim 12-14, 18, 21, 22 are rejected under 35 U.S.C. 102(b) as being anticipated by Kazama.

With regard to claim 12, Kazama (US 6,337,572) discloses (Fig. 2) an electrically conductive contact holder comprising a supporting member (10), with a contacting surface corresponding to a terminal surface of a to-be-contacted member on which a plurality of external connecting terminals are arranged, a plurality of electrically conductive contacts (7,6) being arranged on the contacting surface to be electrically connected to the external connecting

Art Unit: 2833

terminals and accommodated in holder holes, wherein the supporting member includes a high thermal expansion supporting frame (10a) with a coefficient of linear expansion higher than that of the to-be-contacted member; and

a low thermal expansion supporting frame (10b) that is arranged adjacent to the high thermal expansion supporting frame in a direction normal to the contacting surface, and has a coefficient of linear expansion lower than that of the to-be-contacted member.

that the high thermal expansion supporting frame (81) and the low thermal expansion supporting frame (82) are formed so that a coefficient of linear expansion of the supporting member, defined based on the

With regard to claim 13, Kazama discloses that thickness in the normal direction and the coefficient of linear expansion of each of the high thermal expansion supporting frame and the low thermal expansion supporting frame, corresponds to the coefficient of linear expansion of the to-be-contacted member.

With regard to claim 14, Kazama discloses (Fig. 2) that the supporting member (11) is formed so that the distribution of the coefficient of linear expansion thereof is symmetrical about a midplane in the normal direction to the contacting surface.

With regard to claim 18, Kazama discloses electrically conductive contact unit with a contacting surface opposed to a to-be-contacted member, the electrically conductive contact unit comprising:

an electrically conductive contact (6,7) that is arranged on the contacting surface to be electrically connected to an external connecting terminal provided on the to-be-contacted member in use;

a supporting member (10) that includes a high thermal expansion supporting frame (10b) with a

Art Unit: 2833

coefficient of linear expansion higher than that of the to-be-contacted member, and a low thermal expansion supporting frame (10c or 10a) that is arranged adjacent to the high thermal expansion supporting frame in a direction normal to the contacting surface and has a coefficient of linear expansion lower than that of the to-be-contacted member; and a circuit board (2) that is electrically connected to the electrically conductive contact and generates an electric signal supplied to the to-be-contacted member.

With regard to claim 18, Kazama discloses that the high thermal expansion supporting frame and the low thermal expansion supporting frame are formed so that a coefficient of linear expansion of the supporting member, defined based on the thickness in the normal direction and the coefficient of linear expansion of each of the high thermal expansion supporting frame and the low thermal expansion supporting frame, corresponds to the coefficient of linear expansion of the to-be-contacted member, and that the distribution of the coefficient of linear expansion thereof is symmetrical about a midplane in the normal direction to the contacting surface.

With regard to claim 21, Kazama discloses a supporting member (10) formed by stacking a plurality of plate members in layers and a holder hole forming unit set (9) in an opening formed in the supporting member, in which holder holes are formed in the holder hole forming unit to accommodate electrically conductive contacts (6,7) that are electrically connected to external connecting terminals provided on a to-be-contacted member, respectively, Kazama discloses the method comprising:

- forming openings in the respective plate members;
- forming the supporting member by joining the plurality of the plate members formed with the openings in the thickness direction;
- fixing the holder hole forming unit to the inner surface of the opening in the supporting member;

Art Unit: 2833

and forming the holder holes in the holder hole forming unit.

With regard to claim 22, Kazama discloses the plate members are joined together by diffusion bonding (col. 5, lines 6-8), the holder hole forming unit is fixed by soldering (col. 5, lines 13-15), and the forming of the supporting member is performed simultaneously with the fixing.

Claim 12, 14 are rejected under 35 U.S.C. 102(b) as being anticipated by Japanese Document 2002-139513 – inv. Kazama.

With regard to claim 12, Japanese Document 2002-139513 – inv. Kazama disclose (Fig. 5-9) an electrically conductive contact holder comprising a supporting member (11), with a contacting surface corresponding to a terminal surface of a to-be-contacted member on which a plurality of external connecting terminals are arranged, a plurality of electrically conductive contacts (3, 4) being arranged on the contacting surface to be electrically connected to the external connecting terminals and accommodated in holder holes, wherein the supporting member includes a high thermal expansion supporting frame (8) with a coefficient of linear expansion higher than that of the to-be-contacted member; and a low thermal expansion supporting frame (1a, 1b) that is arranged adjacent to the high thermal expansion supporting frame in a direction normal to the contacting surface, and has a coefficient of linear expansion lower than that of the to-be-contacted member.

With regard to claim 14, Japanese Document 2002-139513 – inv. Kazama disclose (Fig. 5-9) that the supporting member (11) is formed so that the distribution of the coefficient of linear expansion thereof is symmetrical about a midplane in the normal direction to the contacting surface.

Art Unit: 2833

With regard to claim 15, Japanese Document 2002-139513 – inv.Kazama disclose (Fig. 5-9) the supporting member further includes

an opening (12) at a region where the electrically conductive contacts are arranged; and a holder hole forming unit that is set in the opening to form the holder holes therein.

With regard to claim 16, Japanese Document 2002-139513 – inv.Kazama disclose an electrically conductive contact holder comprising: a supporting member (11) with an opening (12) formed therein; and an holder hole forming unit set (13) in the opening that includes a holder hole accommodating an electrically conductive contact electrically connected to an external connecting terminal provided on a to-be-contacted member, wherein any one (8) of the supporting member and the holder hole forming unit has a coefficient of linear expansion higher than that of the to-be-contacted member, while the other (1) has a coefficient of linear expansion lower than that of the to-be-contacted member.

With regard to claim 17, Japanese Document 2002-139513 – inv.Kazama disclose that the supporting member is formed of a plurality of plate members having different coefficients of linear expansion, which are stacked in layers in the thickness direction.

With regard to claim 18, Japanese Document 2002-139513 – inv.Kazama disclose electrically conductive contact unit with a contacting surface opposed

to a to-be-contacted member, the electrically conductive contact unit comprising:

an electrically conductive contact (3,4) that is arranged on the contacting surface to be electrically connected to an external connecting terminal provided on the to-be-contacted member in use;

a supporting member (11) that includes a high thermal expansion supporting frame (8) with a coefficient of linear expansion higher than that of the to-be-contacted member, and a low thermal expansion supporting frame (1) that is arranged adjacent to the high thermal expansion

Art Unit: 2833

supporting frame in a direction normal to the contacting surface and has a coefficient of linear expansion lower than that of the to-be-contacted member; and
a circuit board (5) that is electrically connected to the electrically conductive contact and generates an electric signal supplied to the to-be-contacted member.

With regard to claim 20, Japanese Document 2002-139513 – inv.Kazama discloses electrically conductive contact unit with a contacting surface opposed to a to-be-contacted member, the electrically conductive contact unit comprising:

electrically conductive contacts that are arranged on the contacting surface to be electrically connected to external connecting terminals provided on the to-be-contacted member, respectively, in use;

a holder hole forming unit (13) where holder holes are formed to accommodate the electrically conductive contacts;

a supporting member (1a, 1b) that supports the holder hole forming unit; and

a circuit board that is electrically connected to the electrically conductive contacts and generates an electric signal supplied to the to-be-contacted member, wherein

the holder hole forming unit and the supporting member are formed so that one thereof has a coefficient of linear expansion higher than that of the to-be-contacted member, while the other has a coefficient of linear expansion lower than that of the to-be-contacted member.

Claim Rejections - 35 USC § 103

The following is a quotation of 35 U.S.C. 103(a) which forms the basis for all obviousness rejections set forth in this Office action:

(a) A patent may not be obtained though the invention is not identically disclosed or described as set forth in section 102 of this title, if the differences between the subject matter sought to be patented and the prior art are such that the subject matter as a whole would have been obvious at the time the invention was made to a person having ordinary skill in the art to which said subject matter pertains. Patentability shall not be negated by the manner in which the invention was made.

Art Unit: 2833

Claims 13, 19 are rejected under 35 U.S.C. 103(a) as being unpatentable over Kazama in view of Japanese Document 8-5664.

Japanese Document 8-5664 discloses (section 0009) that the high thermal expansion supporting frame (81) and the low thermal expansion supporting frame (82) are formed so that a coefficient of linear expansion of the supporting member, defined based on the thickness in the normal direction and the coefficient of linear expansion of each of the high thermal expansion supporting frame and the low thermal expansion supporting frame, corresponds to the coefficient of linear expansion of the to-be-contacted member.

Therefore, it would have been obvious to one having ordinary skill in the art at the time the invention was made to arrange the frame components , as taught by Japanese Document 8-5664, to match thermal coefficients of the inspection board and IC wafer.

Any inquiry concerning this communication or earlier communications from the examiner should be directed to Alexander D. Gilman whose telephone number is 571 272-2004. The examiner can normally be reached on Monday-Friday, 10:30 a.m. - 8:00 p.m.

If attempts to reach the examiner by telephone are unsuccessful, the examiner's supervisor, Renee S. Luebke can be reached on 571 272-2800 ext. 33. The fax phone number for the organization where this application or proceeding is assigned is 571-273-8300.

Art Unit: 2833

Information regarding the status of an application may be obtained from the Patent Application Information Retrieval (PAIR) system. Status information for published applications may be obtained from either Private PAIR or Public PAIR. Status information for unpublished applications is available through Private PAIR only. For more information about the PAIR system, see <http://pair-direct.uspto.gov>. Should you have questions on access to the Private PAIR system, contact the Electronic Business Center (EBC) at 866-217-9197 (toll-free). If you would like assistance from a USPTO Customer Service Representative or access to the automated information system, call 800-786-9199 (IN USA OR CANADA) or 571-272-1000.

/Alexander D Gilman/
Primary Examiner
Art Unit 2833

9/08/08